





Maximum Working Pressure : 17.0MPa / 2,500PSI

BRIDGESTONE EQ1708

Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
EQ1708-77	1/2	12.7	0.89	22.6	2,500	17.0	12,500	85.0	3.54	90	0.42	630	2W	UB
EQ1710	5/8	15.9	1.04	26.5	2,500	17.0	12,500	85.0	4.33	110	0.57	860		
EQ1712	3/4	19.0	1.14	29.0	2,500	17.0	12,500	85.0	5.51	140	0.66	990		
EQ1716-77	1	25.4	1.42	36.0	2,500	17.0	12,500	85.0	6.30	160	0.95	1,430	4S	UZ HW
EQ1720	1-1/4	31.8	1.79	45.5	2,500	17.0	12,500	85.0	8.27	210	1.71	2,560		
EQ1724	1-1/2	38.1	2.07	52.5	2,500	17.0	12,500	85.0	11.02	280	2.05	3,070		

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +120°C (-40°F to +248°F)
Temperature Range : ambient	-40°C to + 70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

Reinforcement

