









## Maximum Working Pressure : 31.0MPa / 4,500PSI



**BRIDGESTONE EQ3108**

Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
EQ3108-77	1/2	12.7	0.90	22.8	4,500	31.0	22,500	155.0	4.72	120	0.53	800	4S	UB
EQ3110-77	5/8	15.9	1.06	26.8	4,500	31.0	22,500	155.0	6.30	160	0.67	1,000		
EQ3112-77	3/4	19.0	1.17	29.6	4,500	31.0	22,500	155.0	7.87	200	0.75	1,130		
EQ3116-77	1	25.4	1.47	37.4	4,500	31.0	22,500	155.0	9.45	240	1.33	2,000		
EQ3120	1-1/4	31.8	1.93	49.0	4,500	31.0	22,500	155.0	12.60	320	2.53	3,800	6S	UZ
EQ3124	1-1/2	38.1	2.20	55.9	4,500	31.0	22,500	155.0	15.35	390	3.00	4,500		KN
EQ3132	2	50.8	2.95	75.0	4,500	31.0	22,500	155.0	22.05	560	5.27	7,900		EX

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +120°C (-40°F to +248°F)
Temperature Range : ambient	-40°C to + 70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

### Reinforcement

